








| Item | Specification |
|--------------------|---|
| Clear-span width | 20m |
| Eave height | 3.88m |
| Ridge height | 7.1m |
| High Peak height | - |
| Roof pitch | 18° |
| Side length | 6.18m |
| Longest component | 10.7m |
| Roof fixing | Bar tensioning |
| Main profile | 204x120x4mm (4-channel) |
| Wind loading | 100km/hour 0.5kn/m ² |
| Eave connection | Hot-dip Galvanized steel insert |
| Framework material | Hard pressed extruded aluminium 6061/T6 (15HW) |
| Cover material | PVC-coated polyester textile, flame retardant to DIN 4102 B1,M2,CFM. 750g-900g/m ² |

| Optional accessories |
|------------------------------------|
| PVC window sidewalls |
| Anchoring |
| Rain Gutter |
| Lining and curtain |
| Glass door units |
| Transparent PVC cover and sidewall |
| Flooring system |
| Weight plate |

| Framework main profile dimension and use | | |
|--|--|--|
|  <p>upright support Roof Beam</p> |  <p>Gable pole</p> | |
|  <p>Ridge purlin</p> |  <p>Eave purlin</p> |  <p>Gable beam</p> |
| |  <p>Intermediale purlin</p> |  <p>Eave tension rail</p> |

