







| Item | Specification |
|-------------------------|--|
| Clear span width | 20m |
| Side height (1st floor) | 3.35m |
| Eave height | 6.75m |
| Top height | 10.17m |
| Wind loading | 120km/hour |
| Floor Loading Capacity | 450kg/m ² |
| Roof pitch | 18° |
| Main Profile | 300X120X5mm |
| Roof Options | Thermo Roof |
| Roof Fixing | Bar Tensioning |
| Eave connection | Hot-dip Galvanized twin steel plate |
| Framework material | Hard pressed extruded aluminium 6061/T6 (15HW) |
| Cover material | PVC-coated polyester textile, flame retardant to DIN 4102 B1,M2,CFM. 750-900g/m ² |

| Optional accessories |
|------------------------------------|
| PVC window sidewalls |
| Anchoring |
| Rain Gutter |
| Lining and curtain |
| Glass door units |
| Transparent PVC cover and sidewall |
| Flooring system |
| Weight plate |

| Framework main profile dimension and use | | |
|--|--|---|
|  <p>Roof Beam Upright Support Gable Pole</p> |  <p>Gable Pole</p> |  <p>Eave Purlin Ridge Purlin</p> |
|  <p>Eave Purlin</p> |  <p>Intermediate Purlin</p> |  <p>Eave tension rail</p> |

